



SAFETY DATA SHEET

1. Product And Company Identification

SDS ID: SDS 709
 PRODUCT NAME: Prestone® 3 in 1 Windshield Washer Fluid
 PRODUCT NUMBER: AS658
 FORMULA NUMBER: 2593-93

PRODUCT NOT FOR SALE IN CALIFORNIA

MANUFACTURER: Prestone Products Corporation Danbury, CT 06810-5109	CANADIAN OFFICE: FRAM Group (Canada), Inc. Mississauga, Ontario L5L 3S6
---	--

MEDICAL EMERGENCIES AND ALL OTHER INFORMATION PHONE NUMBER:

(800)890-2075 (in the US)
 (800)668-9349 (in Canada)

TRANSPORTATION EMERGENCY PHONE NUMBER (Chemical Spills and Transport Accidents only):

CHEMTREC 1-800-424-9300 (in the US)
 CANUTEC (613)996-6666 (in Canada)

SDS DATE OF PREPARATION/REVISION: 3/23/15

PRODUCT USE: Automobile windshield cleaner/deicer - consumer product
 RESTRICTIONS ON USE: None identified

2. Hazards Identification

GHS/HAZCOM 2012 Classification:

Health	Physical
Acute Toxicity Category 3 (Inhalation, Oral, Dermal) Specific Target Organ Toxicity – Single Exposure Category 1	Flammable Liquid Category 3

Label Elements

DANGER!
 Flammable liquid and vapor.
 Toxic if swallowed, in contact with skin and if inhaled.
 Causes damage to eyes and central nervous system.

Prevention:
 Keep away from heat, sparks, open flames, and hot surfaces. No smoking.
 Keep container tightly closed.
 Ground and bond container and receiving equipment



Use explosion-proof electrical, ventilating, and lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe mists, vapors or spray.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves, protective clothing and eye protection.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
Call a POISON CENTER or doctor if you feel unwell.
Take off contaminated clothing and wash it before reuse.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor.
IF SWALLOWED: Immediately call a POISON CENTER or doctor.
Rinse mouth.
IF exposed or concerned: Call a POISON CENTER, or doctor.
In case of fire: Use water fog, carbon dioxide, alcohol foam or dry chemical to extinguish.

Storage:

Store in a well-ventilated place. Keep cool. Keep container tightly closed.
Store locked up.

Disposal:

Dispose of contents and container in accordance with local and national regulations.

3. Composition/Information On Ingredients

Component	CAS No.	Amount
Non-hazardous Ingredients	Mixture	60-100%
Methyl Alcohol (Methanol)	67-56-1	20-40%

The exact concentrations are a trade secret.

4. First Aid Measures

INHALATION: Remove the victim to fresh air. If breathing has stopped administer artificial respiration. If breathing is difficult, have medical personnel administer oxygen. Get immediate medical attention.

SKIN CONTACT: Remove contaminated clothing. Immediately wash contacted area thoroughly with soap and water. Get medical attention.

EYE CONTACT: Immediately flush eyes with large amounts of water for 15 minutes. Get medical attention if irritation persists.

INGESTION: Seek immediate medical attention. Immediately call local poison control center or go to an emergency department. Never give anything by mouth to or induce vomiting in an unconscious or drowsy person.

MOST IMPORTANT SYMPTOMS: Inhalation may cause headache, dizziness, drowsiness, nausea, visual impairment, narcosis and unconsciousness. Methyl Alcohol may be absorbed through the skin in harmful amounts. Poisonous if swallowed.



INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT, IF NEEDED: Seek immediate medical attention for ingestion; inhalation or skin contact.

NOTES TO PHYSICIAN:

The combination of visual disturbances, metabolic acidosis and an osmol gap is evidence of methanol poisoning. Ethanol is antidotal and its early administration may block the formation of toxic metabolites of methanol. The objective is to rapidly achieve and maintain a blood ethanol level of approximately 100 mg/dl by giving a loading dose of ethanol followed by a maintenance dose. Intravenous administration of ethanol is the preferred route. Ethanol blood levels should be checked frequently. Hemodialysis may be required. Treat acidosis with intravenous sodium bicarbonate. 4-Methyl pyrazole (Fomepizole®), a potent inhibitor of alcohol dehydrogenase, has been used therapeutically to decrease the metabolic consequences of methanol poisoning. Fomepizole® is easier to use clinically than ethanol, does not cause CNS depression or hypoglycemia and requires less monitoring than ethanol. Folic acid may also be administered to enhance the metabolism of formic acid, the toxic metabolite of methanol.

Seek immediate consultation with a physician toxicologist or poison control center.

5. Firefighting Measures

SUITABLE EXTINGUISHING MEDIA: Use water fog, carbon dioxide, alcohol foam or dry chemical. Cool fire exposed containers with water.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL: Flammable liquid. Methanol-water mixtures will burn unless very dilute. Flame is invisible in daylight. Vapors are heavier than air and may flow along surfaces to distant ignition sources and flashback. Burning may produce carbon monoxide and carbon dioxide.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored.

6: Accidental Release Measures

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES: Eliminate all ignition sources. Ventilate area. Wear appropriate protective clothing and equipment (See Section 8).

METHODS AND MATERIALS FOR CONTAINMENT/CLEANUP: Collect with absorbent material and place in a container suitable for flammable waste.

7. Handling and Storage

PRECAUTIONS FOR SAFE HANDLING:

May be fatal or cause blindness if swallowed! Do not swallow. Avoid eye and skin contact. Avoid breathing vapors or mists. Use only with adequate ventilation. Wash exposed skin thoroughly with soap and water after use. Flammable liquid! Keep away from heat, sparks, open flames and all other sources of ignition. Do not smoke during use.

Empty containers retain product residue and may be dangerous. Do not cut, weld, drill, etc. containers, even empty. Do not reuse empty containers unless properly cleaned.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES: Keep away from heat, sparks, open flames and all other sources of ignition. Store in a cool, well-ventilated area.

NFPA CLASSIFICATION: II



8. Exposure Controls / Personal Protection

EXPOSURE GUIDELINES

CHEMICAL	EXPOSURE LIMIT
Non-hazardous Ingredients	None Established PEL/TLV
Methyl Alcohol (Methanol)	200 ppm TWA OSHA PEL 200 ppm TWA ACGIH TLV skin 250 ppm STEL ACGIH TLV

APPROPRIATE ENGINEERING CONTROLS: Use general ventilation or local exhaust as required to maintain exposures below the occupational exposure limits.

RESPIRATORY PROTECTION: For operations where the TLV is exceeded a NIOSH approved supplied air respirator or positive pressure self-contained breathing apparatus is recommended. Organic vapor cartridge respirators are not recommended for methanol vapor exposures. Equipment selection depends on contaminant type and concentration. Select and use in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

GLOVES: Chemical resistant gloves such as butyl rubber or Viton where contact is possible.

EYE PROTECTION: Splash proof goggles are recommended to prevent eye contact.

OTHER PROTECTIVE EQUIPMENT/CLOTHING: Appropriate protective clothing as needed to minimize skin contact.

9. Physical and Chemical Properties

APPEARANCE:	Clear yellow liquid	ODOR:	Citrus
ODOR THRESHOLD:	160 - 690 ppm (Methanol)	pH:	11
MELTING/FREEZING POINT:	< 28°F (< -33.3°C)	BOILING POINT/RANGE:	177°F (80.5°C)
FLASH POINT:	90°F (32.2°C) Setaflash	EVAPORATION RATE: (Butyl Acetate = 1)	Not determined
FLAMMABILITY (SOLID, GAS)	Not applicable	FLAMMABILITY LIMITS:	LEL: 6.0% (Methanol) UEL: 36% (Methanol)
VAPOR PRESSURE:	Not determined	VAPOR DENSITY (air = 1):	Not determined
RELATIVE DENSITY:	0.9425	SOLUBILITIES	Water: 100%
PARTITION COEFFICIENT (n-octanol/water)	Not determined	AUTOIGNITION TEMPERATURE:	Not determined
DECOMPOSITION TEMPERATURE:	Not determined	VISCOSITY:	Not determined

10. Stability and Reactivity

REACTIVITY: Normally unreactive

CHEMICAL STABILITY: Stable

POSSIBILITY OF HAZARDOUS REACTIONS: Reaction with strong oxidizers will generate heat.

CONDITIONS TO AVOID: Heat, sparks, flames and all other sources of ignition.



12. Ecological Information

ECOTOXICITY:

Methanol: LC50 Fathead minnows 29,400 mg/L/96 hr.
EC50 Daphnia magna >10,000 mg/L/24 hr.

PERSISTENCE AND DEGRADABILITY:

Methanol: Readily biodegradable.

BIOACCUMULATIVE POTENTIAL:

Methanol: Estimated BCF of 3 - Potential for bioconcentration in aquatic organisms is low.

MOBILITY IN SOIL:

Methanol has a very high mobility in soil.

OTHER ADVERSE EFFECTS: None

13. Disposal Considerations

Recycle, incinerate, treat or landfill in accordance with all local, state/provincial and federal regulations.

14. Transport Information

U. S. DOT HAZARD CLASSIFICATION (For Ground Shipments Only)

Containers Not Over 5 Liters (1.3 gal.):

PROPER SHIPPING NAME: UN1993, Flammable Liquid, n.o.s. (contains Methanol), 3, PG III, Limited Quantity

TECHNICAL NAME: Methanol

UN NUMBER: UN1993

HAZARD CLASS/PACKING GROUP: 3, III

LABELS REQUIRED: None, Limited Quantity Mark

Note: Until: 12/31/2020 Consumer commodity, ORM-D is also acceptable.

Containers Over 5 Liters: UN1993, Flammable Liquid, n.o.s. (contains Methanol), 3, PG III

DOT MARINE POLLUTANTS: This product does not contain Marine Pollutants as defined in 49 CFR 171.8.

IMDG CODE SHIPPING CLASSIFICATION

Only containers not over 5 Liters can be shipped as Limited Quantities

DESCRIPTION: UN1992, Flammable Liquid, toxic, n.o.s. (contains Methanol), 3 (6.1), PG III, FP 32 C, LTD QTY

ID NUMBER: UN1992

HAZARD CLASS: 3 (6.1)

PACKING GROUP: III

LABELS REQUIRED: None, Limited Quantity Mark Required

PLACARDS REQUIRED: LIMITED QUANTITIES Mark on Cargo Transport Containers

CANADIAN TDG CLASSIFICATION (For Ground Shipments Only)

Containers Not Over 5 Liters:

PROPER SHIPPING NAME: Consumer Commodity (Limited Quantity)

TECHNICAL NAME: None

UN NUMBER: None



HAZARD CLASS: None
PACKING GROUP: None

Containers Over 5 Liters: UN1992, Flammable Liquid, toxic, n.o.s. (contains Methanol), 3 (6.1), PG III

IATA/ICAO SHIPPING CLASSIFICATION: These products are not suitable for shipment by air.

15. Regulatory Information

EPA SARA 311/312 HAZARD CLASSIFICATION: Acute health, chronic health, fire hazard

EPA SARA 313: This Product Contains the Following Chemicals Subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372):

Methanol	67-56-1	20-40%
----------	---------	--------

PROTECTION OF STRATOSPHERIC OZONE: This product is not known to contain or to have been manufactured with ozone depleting substances as defined in 40 CFR Part 82, Appendix A to Subpart A.

CERCLA SECTION 103: Spills of this product over the RQ (reportable quantity) must be reported to the National Response Center. The RQ for the product, based on the RQ for Methanol (40% maximum) of 5,000 lbs, is 12,500 lbs. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CALIFORNIA PROPOSITION 65: This product contains the following chemicals regulated under California Proposition 65:
Methyl Alcohol (Methanol) 67-56-1 20-40% developmental

CALIFORNIA AIR RESOURCE BOARD (CARB) CONSUMER PRODUCT REGULATION: Product not for sale in California.

CANADIAN ENVIRONMENTAL PROTECTION ACT: All of the ingredients are listed on the Canadian Domestic Substances List or exempt from notification.

CANADIAN WHMIS CLASSIFICATION: Class D - Division 1 - Subdivision D –(toxic material causing immediate toxic effects), Class D - Division 2 - Subdivision A - (A very toxic material causing other chronic effects), Class B - Division 2 (Flammable Liquid)



CANADIAN WHMIS HAZARD SYMBOLS:

This SDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the SDS contains all of the information required by the CPR.

EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES (EINECS): All of the ingredients are listed on the EINECS inventory.

KOREA: All of the ingredients of this product are listed on the Korean Existing Chemical List (KECL).

16. Other Information



NFPA Rating: Fire: 2 Health: 3 Instability: 0

REVISION SUMMARY: Section 14: All modes

SDS Date of Preparation/Revision: March 23, 2015

This SDS is directed to professional users and bulk handlers of the product. Consumer products are labeled in accordance with Federal Hazardous Substances Act regulations.

While Prestone Products Corporation believes that the data contained herein are factual and the opinions expressed are those of qualified experts regarding the results of tests conducted, the data are not to be taken as a warranty or representation for which Prestone Products Corporation assumes legal responsibility. They are offered for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

If more information is needed, please contact:

Prestone Products Corporation
69 Eagle Road
Danbury, CT 06810
(800) 890-2075